

Emergency Safety Doors

Our popular and universal Emergency Safety Door fits all tubular columns. Carried as a matter of course, and easily fitted by street lighting patrols, the doors help maintain public safety and prevent further damage to components and circuitry.

The non-conductive doors are moulded from tough 3mm Acrylonitrile Butadiene Styrene (ABS plastic). Fixing is either by re-usable standard zinc plated banding or polyamide. All banding is retained in moulded channels to help minimise danger from sharp edges.

The advantage for you:

- ✓ A quick response to vandalised and damaged columns
- ✓ Fits all curved columns
- ✓ Easily adapted for smaller applications
- ✓ Minimises the danger to the public – quickly
- ✓ Further internal damage contained – quickly



Emergency Door Product codes	Emergency Door Product Description
SD/1 Safety door	Safety Door H637mm x W145mm x D
SD/2 Safety door	Safety Door + zinc plated fixing bands/slotted screws
	Fixings
SD/3 Straps (pair)	2 x zinc plated bands/slotted screws
EPS-8 Banding	Polyamide banding up to 200mm diameter column (pack100)
EPS-14 Banding	Polyamide banding up to 350mm diameter column (pack100)
EPT-96 Fixing tool	Polyamide banding fixing tool



Charles Endirect Safety Products

+44 (0) 1963 828 400 • info@CharlesEndirect.com • www.charlesendirect.com

Charles Endirect Ltd, Wessex Way, Wincanton business Park, Wincanton, Somerset BA9 9RR
 Registration No. 1855059, England Ref 1044 V3 DRAFT Jan21 © all rights reserved